

Built in Australia.

Features heavy duty cast iron pumps in V-twin and W-triple configurations.

- ◆ Rated to AS4637.
- ◆ Heavy duty “close grain” cast iron construction.
- ◆ Featuring highly efficient reed valves.
- ◆ Fully balanced flywheel with large cooling blades.
- ◆ Guarding meets Occupational Health and Safety Standards.
- ◆ Tank meets Australian Standard AS1210.
- ◆ TECO motor with overload protection.
- ◆ Supported by TECO National Service Network.
- ◆ Capacitor start/Capacitor run.
- ◆ Includes filter/regulator kit (C12 & C16).
- ◆ Removable wheels & handle.
- ◆ Full range of spare parts.
- ◆ Warranty.
 - 5 years on pump.
 - 5 years on tank.
 - 1 year on motor and fittings.

Includes Filter/Regulator

Dimensions (mm)	Length	Width	Height	Weight (kg)
C 12	940	335	700	69
C 16	940	335	770	76
C 16/L	1,450	400	850	119
C 22	1,500	500	1,000	171

* Dimensions exclude wheels and handle

Product Code	Displacement CFM	L/min	Free Air Delivery CFM	L/min	Motor Hp	Tank Litres	Power Supply	Max. Pressure	Pump Model	Cylinders
C 12	12.3	348	8.4	238	2.2	60	10 A	130psi	LB 30	V-Twin
C 16	16.0	453	11.6	328	3.0	60	15 A	130psi	LB 40	W-Triple
C 16/L	16.0	453	11.6	328	3.0	125	15 A	130psi	LB 40	W-Triple
C 22	23.6	668	16.3	461	4.0	155	20 A	130psi	LB 50	V-Twin

* 240 volt High Pressure 2 stage - also available



C 12



C16



CFM x 28.3 = Litres per minute
Displacement & FAD calculated at 100 psi.
3.0Hp motors must only be used with 15A power outlet.
Specifications/configuration may change at any time without notice.