

Built in Australia.

4Hp / 20A single phase electric motor.

Features heavy duty, twin cylinder cast iron pump.

240V / 4Hp

- ◆ Rated to AS4637.
- ◆ 4Hp TECO, totally enclosed fan cooled motor.
- ◆ Supported by TECO National Service Network.
- ◆ 1 x start capacitor / 2 x run capacitors.
- ◆ Heavy duty pressure switch with overload protection.
- ◆ Heavy duty “close grain” cast iron pump.
- ◆ Featuring highly efficient reed valves.
- ◆ Fully balanced flywheel with large cooling blades.
- ◆ ½” BSP tank outlet.
- ◆ Guarding meets Australian Occupational Health & Safety Standards.
- ◆ Tank meets Australian Standard AS1210.
- ◆ Full range of spare parts available.
- ◆ Warranty.
 - 3 years on pump.
 - 5 years on tank.
 - 1 year on motor & fittings.



C 22

Dimensions (mm)	Length	Width	Height	Weight (kg)
C22	1,500	500	1,000	171

Product Code	Displacement CFM	L/min	Free Air Delivery CFM	L/min	Motor Hp	Tank Litres	Power Supply	Pump Model	Cylinders
C22	23.6	668	16.3	461	4.0	155	20A	LB 50	V-Twin

* Larger Hp single phase versions available on request

* Portable version available on request



CFM x 28.3 = Litres per minute
 Displacement & FAD calculated at 100psi.
 Specifications/configuration may change at any time without notice.

For improved air quality please consider our Refrigerated Dryers and Filters.