

AF Series – ABAC™ Pumps

Stationary - 415 Volt

Our industrial range of stationary air compressors available from 4 to 10Hp using pumps from the world's largest air compressor manufacturer, ABAC SpA, offering reliable, affordable units with full after sales service. Air compressor tanks made to Australian Standard AS1210. ABAC two stage pumps are far more efficient than single stage pumps where required pressure is 100psi and above.

- Rated to AS4637.
- Efficient two stage, Italian made ABAC pump.
- Cast iron cylinder and crankshaft.
- Two stage, 160psi for high pressure applications.
- Intercooler & aftercooler for cooler, drier air.
- Condor auto stop/start pressure switch.
- Guard design for fan forced cooling.
- Less power usage cheaper to run.
- Motor overload protection.
- Motors rated to MEPS2.
- Full range of spare parts available.
- Warranty.
 - 2 years on pump.
 - 5 years on tank.
 - 1 year on motor and fittings.

Dimensions (mm)	Length	Width	Height	Weight (kg)	
AF 49	1,450	450	890	135	
AF 59	1,500	430	930	176	
AF 60	1,500	430	960	209	
AF 60/L	1,500	620	1,095	316	
AF 70	1,500	620	1,139	329	





Product Code	Displacer CFM	nent L/min	Free Air I CFM	Delivery L/min	Motor Hp	Tank Litres	Pump Model	Cylinders / Stages	Max. Pressure
AF 49	18.0	509	14.8	419	4.0	125	B4900	2/2 Stage	160psi
AF 59	23.0	651	18.4	521	5.5	155	B5900	2/2 Stage	160psi
AF 60	29.2	826	23.3	659	7.5	155	B6000	2/2 Stage	160psi
AF 60/L	29.2	826	23.3	659	7.5	250	B6000	2/2 Stage	160psi
AF 70	42.7	1,208	34.2	968	10.0	250	B7000	2/2 Stage	160psi





CFM x 28.3 = Litres per minute
Displacement & FAD calculated at 100psi.
Specifications/configuration may change at any time without notice.

For improved air quality please consider our Refrigerated Dryers and Filters.